



Skyfol

SSI430

Window film



Energy saving

Saves money on cooling bills



EN 12600 certified

International breakage certification



35 years of experience

One of the longest-operating distributors in the industry



Protection against shards of glass

In case of breakage, the glass is held together



Privacy protection

Grants daytime privacy



Modern appearance

The building gets more beautiful



Light protection

Glare is reduced



Scratch-free

Industrial-grade scratch resistant coating




UV protection

Protects your health and your valuables

Energy saving



Single pane



Save energy with window films!

Tensile strength
33600 psi
232 N/mm²

Break strength
134 lbs/inch
23 N/mm

Puncture strength
103 lbs
458 N

	Single pane
Total Solar Energy Rejected	68%
Visible Light Transmitted	30%
Visible Light Reflected Exterior	44%
Visible Light Reflected Interior	44%
Total Solar Energy Reflected	43%
Total Solar Energy Absorbed	35%
Total Solar Energy Transmitted	22%
SHGC	0,32
UV Rejection	99%
U-Value	5,1
Compatibility	Compatible



Interior/exterior

Interior



Thickness

125 microns



Adhesive

Double adhesive thickness



Scratch Resistant Coating

2nd generation



Sizes available

1.52x30 m (60"x100')



Warranty

10 years



Certification

EN12600



Layers

Multi